





## Armoured gun cabinet with double bit key operated lock

## Item no. 4483.T

- Steel door and frame in compliance with UNI EN 10139 (steel case in compliance with UNI EN 10130, 3 mm thick). 8 mm frame welded to the body. Rounded edges to avoid abrasion. Four holes on the rear and four on the bottom for fixing to the wall and to the floor.
- 6 mm thick steel door, rebated on three sides, protected on the hinge side for pull-resistance. Rotating, hardened and tempered steel hinge pins Ø 8 mm.
- Rotating, tempered, hardened, copper and nickel plated steel made deadbolts resistant to attack: 2 horizontal Ø 25 mm and 2 vertical Ø 25 mm. 2 mm thick manganese plate protecting the lock.
- Triple expansion, high security, 8 gorges, two throws lock in compliance with "Class B" UNI EN 1300 terms i.e. lock is provided with false anti-burglar notches with the minimum 100.000 useful combinations. Equipped with 2 double bit nickel plated brass keys that can be removed only when the door is closed.
- Capacity:12 guns housing for item no. 4483.T





Safety box for ammunitions/objects equipped with a Fai by Viro lock, supplied with 2 keys



High concentration and scratchproof polyethylene gun housing and rack (increased in thickness, that provides the perfect setting of single or double-barreled rifles, even with optical)

ITEM NO.	CAPACITY	EXTERNAL DIMENSIONS cm. <b>H x W x D</b>	INTERNAL DIMENSIONS cm. <b>H</b> x <b>W</b> x <b>D</b>	UNIT WEIGHT kg.	PACKING VOLUME m <sup>3</sup>
4483.T	12 guns housing	150 x 56.4 x 40	130 x 55.8 x 33.4	138.4	0.38